

Size	UM	1 trolley	2 trolley	3 trolley	4 trolley 2x2	4 trolley	6 trolley 2x3	6 trolley tunnel	8 trolley 2x4
Chamber base	cm	143 x129	143 x234	143 x339	273 x234	143x443	273x339	143x652	273x443
Chamber height (electrical)	cm	259	259	259	259	259	259	259	259
Chamber height (steam)	cm	259	259	259	259	259	259	259	259
Chamber height (gas)	cm	284	284	284	284	284	284	284	284
Room height required (electrical)	cm	359	359	359	394	359	394	359	394
Room height required (steam)	cm	359	359	359	394	359	394	359	394
Room height required (gas)	cm	384	384	384	419	384	419	384	419
Trolley size (WxDxH)	cm	100x100x200	100x100x200	100x100x200	100x100x200 *	100x100x200	100x100x200	100x100x200	100x100x200 *
Trolley stick length	cm	100	100	100	100	100	100	100	100

Heating capacity

Electrical heating	KW	36	72	108	144	144	216	216	288
Steam heating	KW	40	80	120	160	160	240	240	320
Gas heating	KW	40	80	120	160	160	240	240	320

Smoking generator

Model		GR12	GR24	GR24	GR24	GR24	GR58	GR58	GR58
External dimensions (WxDxH)	cm	54x60x259	74x80x203	73x80x190	73x80x190	73x80x190	95x101x219	95x101x219	95x101x219
Power consumption	KW	1.6	2.3	2.3	2.3	2.3	3.5	3.5	3.5
Sawdust size	mm	0-3	0-3	0-3	0-3 **	0-3	0-3	0-3	0-3 **
Power consumption without heating	KW	7.7	10.4	13.1	15.8	15.8	22.4	22.4	27.8
Low pressure steam consumption	kg/h	40	80	120	160	160	240	240	320
High pressure steam consumption	kg/h	50	100	150	200	200	300	300	400

Cooling capacity

For cold smoke - 5°C	KW	5	10	15	20	20	30	30	40
For intensive cooling -10°C	KW	18	36	54	72	72	108	108	144

* other dimensions on request

** 3-8 mm on request